



**NANOBARRERA**<sup>TM</sup>  
**THERMAL COATINGS**

[www.nano-barrera.com](http://www.nano-barrera.com)

# TI20 THERMOACOUSTIC

## DESCRIPTION

Thermal insulation system (cold/heat), noise absorption, and corrosion control is an advanced and versatile solution for industrial and commercial applications. It is designed to deliver high performance in terms of thermal insulation, noise reduction, corrosion protection, and resistance to moisture.



## FEATURES

- **Thermal Conductivity:** TI20 Thermoacoustic exhibits exceptionally low thermal conductivity, ensuring high efficiency in thermal insulation by significantly reducing heat transfer.
- **Noise Reduction:** TI20 Thermoacoustic provides noise absorption, minimizing acoustic discomfort from resonance, impact, and sound conduction.
- **Corrosion Resistance:** TI20 Thermoacoustic offers effective corrosion protection, acting as a protective barrier to prevent damage from corrosive agents such as moisture, chemical substances, and other environmental factors.
- **Mechanical Stability:** Thanks to its high molecular weight and excellent mechanical stability, the system ensures prolonged durability and resistance to deformations, ensuring reliable long-term performance.
- **Sustainability:** TI20 Thermoacoustic is environmentally friendly, meeting the most stringent sustainability standards, with low VOC emissions and eco-friendly characteristics.

# T120 THERMOACUSTIC



## PROPERTIES

Water-based polymer with a semi-liquid consistency in the wet state, excellent mechanical stability, high molecular weight, antimicrobial activity, germicidal nanocompounds, anti-fungal properties, and controlled addition of low thermal conductivity aggregates, free from thermal bridges, and 100% environmentally friendly.



## USES AND APPLICATIONS

Suitable for industrial, commercial, and residential construction, for interior applications on various surfaces such as wood, metal, concrete, plaster, brick, and block. Apply in thin layers using a brush, a brush, or pneumatic spray equipment.



## TECHNICAL SPECIFICATIONS

COLOR	Light grey
DENSITY	28.08lb/ft <sup>3</sup> (450.0 Kg /m <sup>3</sup> )
MOISTURE ABSORPTION	0.5983% Volume
WATER VAPOR PERMEABILITY	15.49 perms
THERMAL CONDUCTIVITY	0.076 W/m.K.
VOC	< 0.4172 lb/gal
p.H.	7.0 to 9.0
COVERAGE RATE	0.00041 gal/ft <sup>2</sup> 0.00041gal/ft <sup>2</sup> to 0.00130gal/ft <sup>2</sup>
PACKAGE	5 gallon pail (19 liters)

## PRECAUTIONS

- Do not add water



# T120 THERMOACUSTIC



## STORAGE AND SHELF LIFE

Shelf life of 6 months from manufacture date when properly stored in a warehouse between 41°F and 90°F



## APPLICATION METHOD

### SURFACE PREPARATION:

1. Sweep and pressure wash the surface.
2. Apply primer membrane.

### APPLICATION METHODS:

1. Stir contents at low speed until well-mixed.
2. Apply in thin layers using a brush, roller, paintbrush, airless sprayer, or pneumatic spray equipment.
3. For concrete or cement roofs, it's recommended to lay a reinforcing membrane.

### APPLICATION CONDITIONS:

Do not apply when rain is expected or under extreme temperatures.

### LEGAL DISCLAIMER AND LIABILITY LIMITATION:

T120 Thermoacoustic is a product of Nanobarrera™. Any information, data, or designs contained in this document may not be altered and is provided with the intention of offering technical information about the product. The use of T120 thermoacoustic is at the user's own risk and responsibility. The information in this technical sheet is given in good faith and is based on tests and data available up to the document's preparation date. However, the manufacturer does not guarantee the accuracy, completeness, or suitability of this information for specific purposes. Users assume the responsibility of assessing the product's suitability for their specific application and must adhere to all usage and application instructions provided by the manufacturer. Nanobarrera™ and its distributors will not be held accountable for any direct, indirect, special, consequential, or incidental damages that may arise from using or the inability to use the product, even if they've been advised of the potential for such damages. This includes, but is not limited to, property damage, personal injury, or economic losses. The user is responsible for adhering to all applicable standards, regulations, and requirements concerning the product's installation, use, and handling. It's advised to follow all safety precautions and wear appropriate personal protective equipment when handling and applying the product. Any claims related to T120 Thermoacoustic will be limited to either replacing the defective product or refunding the purchase price, at the manufacturer's discretion. For additional technical advice or to address any concerns related to the product's use, it is recommended to consult [www.nano-barrera.com](http://www.nano-barrera.com) or a qualified professional. By using T120 Thermoacoustic, the user agrees to all terms and conditions set forth in this legal disclaimer and liability limitation.